

# RSC-1JG2



Rackmount Storage Chassis

ENCLOSURE SOLUTIONS GROUP (ESG)

## Applications

Database Server


File Server

NAS / iSCSI

Web Server



1U 4-bay



1U 6-bay



1U 8-bay


Dimensions (W x D x H)  
(with chassis ears/protrusions)

mm : 482.6 x 700 x 44.4  
inches : 19 x 27.5 x 1.75


Bezel



Front View



Top View



Rear View



## Features & Benefits

- 1 Front bezel with key lock for data security and protection
- 2 Power on/off, system reset and LEDs for Power, HDD & LAN
- 3 Front access USB port
- 4 One(1) slim CD-ROM/DVD-ROM bay supported
- 5 Four(4), six(6) or eight(8) external 2.5" hot-swap HDD tray w/ lock supported
- 6 Dedication fan access door for hot-swap fan removal
- 7 Five(5) hot-swap middle fans for optimize cooling
- 8 Single or hot-swap redundant high efficiency (>84%) power supply (1+1 module) maximizes server protection options
- 9 One(1) PCI slot via riser card



# SPECIFICATIONS

Industry Standard : EIA-RS310D	
Materials : Heavy-duty preplated SPGC cold-rolled steel	
Finish :	Front Panel: Texture-coated
Cooling :	Middle : 5 x 40x56mm or 4 x 40x56mm + 1 x 40x28mm or 5x 4028mm hot-swap fans
Power Supply :	50E 500W EPS 80+
	50R 500W 1+1 hot-swap redundant 80+
	65R 650W 1+1 hot-swap redundant 80+
	65D 650W 1+1 hot-swap DC redundant
Expansion : 1 x PCI slot via riser card (full height, full length)	
Controls : Power on/off, system reset and 1 x USB port	
Indicators : Power, LAN and HDDs	
System Board : 12"(W) X13"(D) E-ATX/SSI EEB 3.6 compliant MB	
Drive Bay :	5.25" 0
	3.5" 0
	3.5" hot-swap 0
	2.5" hot-swap 4, 6 or 8

Drive Bay :	Internal	3.5" HDD	0
		2.5" HDD	0
		Slim CD-Rom/DVD-Rom	1
		Slim FDD	0
Temperature : 0°C(32°F) ~ 50°C(122°F)			
Humidity : 5%~95% non-condensing			
Gross Weight : 21kgs / 46.2lbs (w/ PSU & Rail)			
Packaging Dimension (W x D x H) :		mm : 580 x 1040 x 250	
Cubic Feet : 5.5			
Reference Container Loading :	20'	170	
	40'	355	
	40' H	425	
Backplane :	BKP-SAS3-2XSFF-R	2-in-1 SAS/SATA 6G for 2.5" G HDD b/p	
	BKP-SAS3-10SGPIO-R	10-in-1 SAS/SATA 6G with SGPIO for 2.5" G HDD b/p	
Riser Card Options :	RCD-1U1PCI32R	RCD-1U1PCI32RIB	
	RCD-1UARC-PEX8-R	RCD-1UARC-PEX16H1-R	
Mounting Option :	SLR-TL28G-TW-AR		

## Ordering Information

Part Numbers	Descriptions	
RSC-1JG2-50E-SAS2-4-R	1U with 500W EPS 80+ power supply, 4x2.5 bays, SAS 6G 2-in-1 BP	
RSC-1JG2-50R-SAS2-4-R	1U with 500W redundant 80+ power supply, 4x2.5 bays, SAS 6G 2-in-1 BP	
RSC-1JG2-65R-SAS2-4-R	1U with 650W redundant 80+ power supply, 4x2.5 bays, SAS 6G 2-in-1 BP	
RSC-1JG2-65D-SAS2-4-R	1U with 650W DC redundant power supply, 4x2.5 bays, SAS 6G 2-in-1 BP	
RSC-1JG2-50E-SAS10-8-R	1U with 500W EPS 80+ power supply, 8x2.5 bays, SAS 6G 10-in-1 BP with SGPIO support	
RSC-1JG2-50R-SAS10-8-R	1U with 500W redundant 80+ power supply, 8x2.5 bays, SAS 6G 10-in-1 BP with SGPIO support	
RSC-1JG2-65R-SAS10-8-R	1U with 650W redundant 80+ power supply, 8x2.5 bays, SAS 6G 10-in-1 BP with SGPIO support	
RSC-1JG2-65D-SAS10-8-R	1U with 650W DC redundant power supply, 8x2.5 bays, SAS 6G 10-in-1 BP with SGPIO support	
Optional Part Numbers	Descriptions	
RSC-1JG2-50E-SAS2-6-R	1U with 500W EPS 80+ power supply, 6x2.5 bays, SAS 6G 2-in-1 BP	
RSC-1JG2-50R-SAS2-6-R	1U with 500W redundant 80+ power supply, 6x2.5 bays, SAS 6G 2-in-1 BP	
RSC-1JG2-65R-SAS2-6-R	1U with 650W redundant 80+ power supply, 6x2.5 bays, SAS 6G 2-in-1 BP	
RSC-1JG2-65D-SAS2-6-R	1U with 650W DC redundant power supply, 6x2.5 bays, SAS 6G 2-in-1 BP	
Replacement Parts	Part Numbers	Descriptions
Fan	FAN-4056/1DG-SD-MOR	SD 4056 HOT-SWAPPABLE FAN MODULE
	FAN-4025/1DG-SD-MOR	SD 4025 HOT-SWAPPABLE FAN MODULE
Fan Board	FBD-1DG-R	FAN BOARD FOR 1DG
Mounting Rail	SLR-TL28G-TW-AR	28" TOOL-LESS RAIL FOR G-SERIES CHASSIS
HDD Carrier	HDT-G25-R	STANDARD G-SERIES DRIVE CARRIER FOR 2.5 INCH SAS/SATA DRIVE
Dummy Cover	HDT-COV-1G25-R	SINGLE DUMMY COVER FOR 2.5 INCH G TRAY
Power Supply	PSU-1SR500E-Z1DG-R	M1S2-5500V 1+1 500W REDUNDANT HIGH EFFICIENCY POWER SUPPLY (85%+)
	PSU-1S500E-Z1DG-R	P1H-5500V 500W SINGLE POWER SUPPLY
	PSU-1SR650E-Z1UG-R	M1U2-5650V 1+1 650W REDUNDANT HIGH EFFICIENCY POWER SUPPLY
	PSU-1SR650ED-Z1UG-R	DM1U2-5650V 1+1 650W REDUNDANT DC POWER SUPPLY
Power Supply Module	PSM-1SR500E-Z1DG-R	M1S2-5500V 1+1 500W REDUNDANT POWER SUPPLY MODULE

Remark: All specifications and photos are subject to change without notice.