


RSC-5D-2Q1

Applications

- Database Server
- Enterprise Storage Server
- Near-Line Storage Server
- Virtual Tape Library
- NAS / iSCSI
- Medical Imaging
- Digital Content Delivery



Features & Benefits

- 1 Superior cooling through front air intake
- 2 Forty-eight(48) bi-color LED for hard drive status - solid blue for power, blinking blue for activity & solid red for failure
- 3 Power on/off, system reset and LEDs for HDD & LAN
- 4 Front access USB port
- 5 Forty-eight(48) 3.5-inch hot-swap HDD supported
- 6 Three(3) hot-swap rear fans modules for 9 x 40x56mm fans for optimized cooling
- 7 Four(4) rear fans for optimized cooling
- 8 Rear access power supply alarm reset
- 9 Rear access power supply control : power on/off, system reset
- 10 Seven(7) PCI slots attribute to network expansion and scalability
- 11 Hot-swap redundant power supply (3+1 module) maximizes server protection

Model Number : RSC-5D-2Q1	
Order Information : RSC-5D-●-2Q1	
Industry Standard : EIA-RS310D	
Materials : Heavy-duty cold-rolled steel	
Finish :	Inside / Body : Zinc-plated with bright chromate
	Outside / Front : Texture-coated
Dimensions : (W x D x H)	mm : 482.6 x 872 x 222
	inches : 19 x 34 x 8.75
Cooling :	Rear: 9 x 40x56mm hot-swap fans for HDD bays + 4 x 60 x 38mm fans for MB
Power Supply :	● Descriptions
	135R 1350W 3+1 redundant power supply (4 x 500W modules)
Expansion : Up to 7 x PCI slots (full height, full length) (depends on the MB)	
Controls : Power on/off, system reset + USB port	
Indicators : Power, LAN and HDD LEDs	
System Board : 116"(W) x 13"(D) Tyan® S4985™ Quad Opteron™ M/B or 16"(W) x 14"(D) Iwill® QK8S™ Quad Opteron™ M/B	

Drive Bay :	External	5.25"	0
		3.5"	0
		3.5" hot-swap	48
		2.5" hot-swap	0
	Internal	3.5"	0
		Slim CD-Rom/DVD-Rom	0
	Slim FDD	0	
Temperature : 0°C(32°F) ~ 50°C(122°F)			
Humidity : 5%~95% non-condensing			
Gross Weight (lbs) : 52 kgs / 114.4 lbs			
Packaging Dimension (W x D x H) :		mm : 600 x 1200 x 490	
Cubic Feet : 12.5			
Reference Container Loading :	20'	70	
	40'	150	
	40' H	180	
Mounting Options :	SLR-28-KS (included)		

Mechanical Drawing

